

# CTM POTTERS SUPPLIES

## SAFETY DATA SHEET

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product information:**

Product Name : Spodumene  
Chemical Name : Sodium, potassium and lithium, aluminium silicates  
Synonyms : None  
Company : CTM Potters Supplies  
Unit 10A, Millpark Industrial Estate  
White Cross Road  
Woodbury Salterton  
Nr. Exeter  
EX5 1EL  
Telephone : 01395-233-077  
Fax : 01395-233-905

---

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS Number	EC Number	% of composition
Complex mixtures of naturally occurring silicates.		Refer to summary.	100%

---

### 3. HAZARD IDENTIFICATION

**Inhalation:** Excessive exposure may cause symptoms of chronic lung disease.  
**Ingestion:** The product is of low solubility in body fluids and it is likely to be of low acute toxicity.  
**Eyes:** May cause physical irritation and inflammation.  
**Skin:** May cause irritation and inflammation.

---

### 4. FIRST AID MEASURES

**General Recommendations:**

**Inhalation:** Remove patient to fresh air, loosen tight clothing and seek medical attention.  
**Ingestion:** Do not induce vomiting. Seek medical advice.  
**Eyes:** Wash immediately with copious amounts of water.  
**Skin:** Wash affected areas with water.

---

### 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** The material is not combustible and no threat to the surrounding fire conditions.  
**Special exposure hazards:** None  
**Protective personal equipment:** None other than those suitable for the surrounding fire conditions.

---

**6. ACCIDENTAL RELEASE MEASURES**

<b>Leaks &amp; Spills:</b>	Collect dry material by wet sweeping or vacuum with an efficient particular filter.
<b>Personal protective equipment:</b>	Respiratory protective equipment.

---

**7. HANDLING AND STORAGE**

<b>Handling:</b>	Do not eat, drink, or smoke in areas where the material is used. Wash thoroughly after handling the material.
<b>Storage:</b>	Store in dry area.

---

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

<b>Engineering controls:</b>	Adequate ventilation should be provided so that Occupational Exposure Limits are not exceeded. Local Exhaust Ventilation is normally recommended.
<b>Personal protective equipment:</b>	Where LEV is not practicable and exposure is likely to be excessive, approved respiratory protection to CEN standards prEN 140, 141, 143 or 149 should be worn. Protective gloves and overalls are recommended for prolonged contact.

---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance:</b>	
Form:	powder
Colour:	fawn
Odour:	odourless
Flash point (°C):	N/A
Flammability:	N/A
Explosive properties:	Non-explosive
Oxidising properties:	Non-oxidising
Specific gravity:	2 – 4 typically
pH value:	8 typically
Melting point (°C):	Starting at approximately 1150°C

---

**10. STABILITY AND REACTIVITY**

<b>Chemical stability:</b>	The material is stable under normal conditions.
<b>Conditions/materials to avoid:</b>	None known
<b>Hazardous decomposition products:</b>	None known
<b>Hazardous polymerization products:</b>	None

---

**11. TOXICOLOGICAL INFORMATION**

<b>Acute toxicology:</b>	LD50 Oral: Not known LD50 Dermal: Not known LD50 inhalation: Not known
<b>Health effects:</b>	Prolonged or repeated exposure above Occupational Exposure Standards may cause fibrosis of the lungs.

---

**12. ECOLOGICAL INFORMATION**

<b>Ecotoxicity:</b>	No specific information available.
<b>Persistence:</b>	The material is insoluble in water.

---

**13. DISPOSAL CONSIDERATIONS**

Dispose in accordance with current waste disposal regulations (for UK – Control of Pollution (Special Waste) Regulations 1980). Landfill is the most appropriate method.

**14. TRANSPORT INFORMATION**

UN/SI No.		Not classified
UN Class		Not classified
Packing Group		Not classified
Road	UK	Not classified
	ADR	Not classified
Sea	IMO	Not classified
Air	ICAO	Not classified

**15. REGULATORY INFORMATION**

<b>EC Supply Labelling:</b>	Non hazardous		
<b>R-Phrases:</b>	None		
<b>S-Phrases:</b>	Optional for dusty powders		
	S20/21	when using do not eat, drink or smoke.	
	S38	in case of insufficient ventilation wear suitable respiratory equipment.	
<b>UK Occupational exposures limits*:</b>	Mg/m <sup>3</sup>	8 hr TWA	% in product.
Dusts -			
Total inhalable		10	
Total respirable		5	

\*Refer to HSE Guidance note EH40

In accordance with HSE Approved Code of Practice for CHIP, the recipient is reminded of their obligations under both the Health and Safety at Work Act (HSWA) and the Control of Substances Hazardous to Health Regulations (COSHH), and that the information in any safety data sheet does not constitute the user's assessment of workplace risk.

**16. OTHER INFORMATION****Summary per product:**

Ref	Description	Colour	CAS	EINECS
106	Spodumene	Fawn	12068-40-5	2350986

**References:**

COSHH ACOP	HSC approved Code of Practice for the Control of Substances Hazardous to Health Regulations 1994
CHIP 96	Chemicals (Hazard Information and Packaging for Supply) Regulations 1996
CHIP SDS ACOPS	HSC Approved Code of Practice for Safety Data Sheets in accordance with regulation 6 of the CHIP regulations.
HSE EH40	HSE Guidance note EH40 on Occupational Exposure Limits to be used in conjunction with the COSH regulations.

**Further information:**

Data sheet producing department: CTM Potters Supplies  
Telephone: 01395-233-077

**Disclaimer:**

The information contained in this safety data sheet has been prepared using the best available information, however in view of technical developments, this may alter. The material must only be used for its stated purpose and the information contained within this data sheet is offered solely for use in the evaluation of this product in respect of safety, health and environmental hazards. Due to the many factors outside our control when using this product, we cannot accept liability for any injury, accident, loss or damage caused through its use.